



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁷ : B66D 1/74</p>	<p>A1</p>	<p>(11) International Publication Number: WO 00/12423 (43) International Publication Date: 9 March 2000 (09.03.00)</p>
<p>(21) International Application Number: PCT/GB99/02798 (22) International Filing Date: 25 August 1999 (25.08.99) (30) Priority Data: 9818921.0 28 August 1998 (28.08.98) GB (71) Applicant (for all designated States except US): LEWMAR MARINE LIMITED [GB/GB]; Southmoor Lane, Havant, Hampshire PO9 1JJ (GB). (72) Inventor; and (75) Inventor/Applicant (for US only): ALLEN, Peter, George [GB/GB]; 77 The Keep, Portchester, Fareham, Hampshire PO16 9PW (GB). (74) Agents: HARRISON, David, Christopher et al.; Mewburn Ellis, York House, 23 Kingsway, London WC2B 6HP (GB).</p>		<p>(81) Designated States: AU, CA, GB, NZ, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i></p>
<p>(54) Title: WINCH AND WINCH DRUM</p> <div data-bbox="483 1144 1177 1774" data-label="Image"> </div> <p>(57) Abstract</p> <p>Rope-holding characteristics of a winch drum (2) are determined by a staggered array of pyramidal protuberances (12, 14, 17, 19) on its surface. The staggering is such that there is no true circular path round the drum within the array, and a rope wound on it in the hoop direction is deflected sinusoidally.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

WINCH AND WINCH DRUM

The present invention relates to winches and winch drums and in particular to winch drum surface
5 finishes.

Winches are commonly used in marine applications to control the length or slackness of a rope acted on by the rotatable drum of the winch. An important feature of the winch drums of such winches is
10 the finish applied to the rope-gripping surface of the drum. Different types of finish produce different grip characteristics. However, because a given finish will always cause rope wear, in practice the choice of a particular finish for a given application will often
15 represent a compromise between grip and wear.

One conventional finish is provided by shot-peening. In this process, small hard objects (typically ceramic grit) are fired at the grip surface of the winch drum. The result is a random arrangement
20 of relatively fine (in relation to the dimensions of the drum) peaks and troughs on the grip surface of the winch drum.

Peened finishes provide good gripping characteristics and controlled letting-off of rope, but
25 have a tendency to promote premature rope wear. In addition, the quality of the peened finish can be

variable. That is, peened finishes are susceptible to variations caused by e.g. changes to the velocity and direction of the peening objects. Subsequent processing can also affect the finish. For example,
5 chrome plating onto a peened brass surface will tend to "soften" the finish of the brass surface. Thus there are many factors which can make it difficult to maintain the reproducibility of peened finishes.

It is also difficult to quantify the essential
10 parameters of any particular finish (meaning those parameters which determine grip and wear) because of the essentially random nature of the arrangement of peaks and troughs. This can be a particular disadvantage if it is desired to investigate
15 systematically the effects of different finishes on rope grip and rope wear, e.g. by varying systematically the parameters of the finish.

Another known finish consists of having an arrangement of vertical slots or ribs on the grip
20 surface of the drum. The slots or ribs are generally parallel to the axis of rotation of the drum, i.e. perpendicular to the winding direction of the rope. However, the grip provided by this type of finish tends to be too strong so that when controlled release of the
25 rope is attempted from the winch, large quantities of rope are let off at a time rather than an even, slow

feed-off.

FR-A-1214874 shows an auxiliary windlass for a fishing boat where frusto-conical projections are arranged on the drum in planes normal to the axis of rotation of the drum, with gap planes between them. The projections are to mesh with a fishing net being drawn onto or leff off from the boat. They do not engage the rope.

With an aim of providing a rope-gripping surface finish whose parameters are both measurable and adjustable, while also providing good rope control and acceptable rope wear, the present invention provides a winch drum in which the finish of a rope-gripping surface is provided by a regular staggered array of protuberances which are of generally pyramidal shape. Note that the term "pyramidal" is not to be construed as being limited to square-based pyramidal shapes, i.e. tetrahedra and other polygonally-based pyramidal shapes are also included. Preferably, circumferentially nearest-neighbour protuberances are staggered in the axial direction of the drum; in other words, the only array of protuberances is a staggered one. If as is also preferred there are no circular paths normal to the axis of rotation of the drum (the hoop direction of the drum), the effect is that a rope wound in the hoop direction around the drum experiences spaced axial

forces on opposing and alternate sides so that the rope tends to follow to some extent a sinusoidal or otherwise snaking path. Faces of the pyramidal shapes may be concavely curved so that respective, radially innermost, edges of adjacent, corner-sharing protuberances form continuous, smooth junctions which prevent a rope wedging fast in the junctions. The pyramidal shapes may be produced by machining on a CNC lathe, but other production techniques, such as casting or pressing, can also be used. For convenience the pyramidal shapes will hereafter be referred to simply as pyramids.

By varying the height, base shape and size (i.e. the characterizing parameters) of the pyramids, it is possible to exert a high degree of control over the surface finish and its effects. In addition these characterizing parameters are readily quantifiable so that it is possible to correlate measurable characteristics of the surface finish with the performance of the finish. This permits a methodical approach to the optimization of the rope-gripping surface finish to be undertaken.

Furthermore, compared with solely peened finishes, quality control of the regularly patterned finish is much improved, as a high degree of control can be exerted over the machining or other operation

which produces the finish.

In a preferred form of the rope-gripping surface, the protuberances are diamond-based pyramids, the regular pattern being formed from a tessellation of the diamond bases of the pyramids. Desirably the pyramids are arranged so that the long direction of the base of the pyramids is aligned to the hoop direction of the winch drum. It is found that such an arrangement can provide a good compromise between rope control and rope wear.

The present invention will now be described in relation to a specific embodiment and with reference to the following figures in which:

Fig. 1 shows a side view of a winch with a winch drum;

Fig. 2 shows a transverse section through the drum on the plane A-A; and

Fig. 3 shows a transverse section through the drum on the plane B-B.

Fig. 1 shows a winch 1 on which is rotatably mounted a winch drum 2 having a skirt 4 and a rope-gripping surface 6 positioned between upper and lower lips 8,10. The rope-gripping surface is essentially cylindrical, of modified circular cross-section.

In use, the winch 1 is secured by its base 9 to a surface such as the deck of a yacht with the axis of

rotation of the drum perpendicular to the surface, and a rope is wound around the rope-gripping surface, in single or multiple loops, the lips 8,10 preventing the rope from riding off the surface 6. Drive to rotate the drum can be applied from the head 11 of the winch, or from below the deck in conventional manner.

The surface 6 of the drum has a finish which comprises a regular pattern of diamond-based pyramidal protuberances. The apexes of the pyramids point radially outwardly and the long direction of the diamond bases of the pyramids are arranged parallel to the hoop direction of the drum 2 i.e. normal to the axis of rotation of the drum. The faces of the pyramids are gently concave and circumferentially nearest-neighbour pyramids are formed in zig-zag chains in the hoop direction of the drum. In other words, valley diamond edges of adjacent pyramids are coincident and form a network of zig-zag paths round the circumference of the drum. See, e.g. coincident valley edge 15 between peaks 17,19 which are thereby staggered relative to the hoop direction.

The pyramids produce an arrangement of peaks, troughs and ridges on the rope-gripping surface 6, which arrangement prevents the rope from uncontrollably sliding over the surface. Smooth and continuous junctions 15,16 are formed between respective joining

edges of adjacent corner-sharing pyramids and axial
ridges and faces of the pyramids are concavely curved
(see, for example, the adjacent corner-sharing pyramids
12,14, viewed side on in Fig. 1). Note how the concave
5 axial ridges 13 of axially-adjacent pyramids merge to
form an essentially smooth arc.

By varying one or more dimension (e.g. pyramid
height or base area) it is possible to optimize the
grip between the surface 6 and a given type of rope,
10 and to suit the drum material. In the present
embodiment the longest dimension of the diamond base of
each pyramid is approximately 20 mm, and the radial
height of each pyramid is about 1.6 mm from the
inscribed circle 20 (Figs. 2 and 3).

15 Figs. 2 and 3 show transverse sections of the
drum at positions A-A and B-B respectively, the dot-
dashed straight lines representing fixed spatial
coordinate axes intersecting at the axis of rotation 22
of the drum. Clearly, as between section A-A and B-B,
20 the relative positions of the peaks and troughs of the
pattern are interchanged; compare peaks 24,26 in Fig. 2
and peak 23,25 in Fig. 3. In this embodiment there are
three peaks in each quarter of the circumference.
Straight lines join peaks 23,25 and peaks 24,26 and are
25 the circumferential ridges of the respective pyramids.

However, the straight lines are intersected at

their mid-points by the zig-zag valley paths 15. The cross-section of the drum surface includes therefore a series of parallel polygons with axially-adjacent neighbours offset relative to each other.

5 A rope wound round the drum is prevented from following an unperturbed hoop path around the drum because of the staggered pattern of protruberances. That is, the rope experiences spaced axial forces on alternate sides to an extent which compel it to follow
10 a snaking path around the peaks of the pyramids. Also as the rope rides over the edges of the pyramids (for instance at edges 13), the edges bite into the rope to provide a controlled amount of grip.

 Therefore, we believe that, as a result of the
15 finish, the gripping force on the rope is part frictional and part mechanical in origin (ignoring here rope-to-rope interactions). In contrast, the gripping force on a rope from a solely peened finish is almost entirely frictional, as the peaks and troughs of a
20 solely peened finish are at least an order of magnitude smaller than a typical rope diameter. For this reason, wear of ropes running over such peened surfaces is much greater. Of course, superficial surface finishes may if desired be applied to the surface of the present
25 drum.

By optimizing the shape and dimension of the

pyramids, a surface finish can be arrived at that represents a good compromise between rope wear, grip and controlled let-off. That is, different shapes and dimensions of pyramids will be suitable for different sizes of winch and thicknesses of rope, but by adjusting these characterizing parameters in a systematic manner, the optimum finish for a given combination of winch and rope can be found.

Claims

1. A winch drum for rotation about an axis, a rope-receiving surface of the drum having a regular axially-staggered pattern of protuberances of generally pyramidal shape.
2. A winch drum according to claim 1 where faces of the pyramidal shapes are concave.
3. A winch drum according to claim 2 wherein axial ridges of the pyramidal shapes are concave.
4. A winch drum according to claim 3 wherein the axial ridges of axially-adjacent protuberances form a single smooth arc.
5. A winch drum according to any one of the preceding claims wherein circumferentially nearest-neighbour protuberances have coincident edges and are staggered in the axial direction of the drum.
6. A winch drum according to any one of the preceding claims, wherein the protuberances have diamond-shaped bases.

7. A winch drum according to claim 6 wherein the major dimension of the diamonds is circumferentially of the drum.

5 8. A winch incorporating a winch drum according to any one of the preceding claims.

9. A winch according to claim 8 which has a base for securing to a deck with the axis of rotation of the
10 drum perpendicular to the deck.

10. A method of holding a rope on a drum of a winch which includes of causing the rope to lie with a sinusoidal path around the drum by passing between
15 axially-staggered pyramidal protuberances on the surface of the drum.




Fig. 2





Fig. 3



INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 99/02798

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B66D1/74

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B66D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 688 765 A (GUANGORENA) 25 August 1987 (1987-08-25) the whole document ----	1,8,10
A	EP 0 637 565 A (MEISSNER ENGINEERING) 8 February 1995 (1995-02-08) ----	
A	WO 94 06710 A (MAXWELL WINCHES) 31 March 1994 (1994-03-31) ----	
A	US 4 274 606 A (BERNWALL) 23 June 1981 (1981-06-23) ----	
P,A	EP 0 887 302 A (LEWMAR MARINE) 30 December 1998 (1998-12-30) -----	

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

8 December 1999

Date of mailing of the international search report

15/12/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Van den Berghe, E

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/GB 99/02798

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4688765	A	25-08-1987	NONE	
EP 637565	A	08-02-1995	NL 9301178 A US 5593140 A	01-02-1995 14-01-1997
WO 9406710	A	31-03-1994	AU 4986893 A	12-04-1994
US 4274606	A	23-06-1981	NONE	
EP 887302	A	30-12-1998	NONE	